


TECHNICAL DATA:

- To Transit pipe load to supports or hangers without crushing insulation
- Dimensionally Accurate - machine Moulded
- With Tongue and Groove Joints to prevent ingress of Air
- Proof against rotting and termite attack
- No distortion or cracking
- Minimise transmission of noise and vibration from pipes to building structure
- Prevent condensation on hangers and supports
- **ECO-FRIENDLY** It is no longer necessary to cut trees just to support pipes

Material: Hard Rubber- Density: 1400 Kg/cuM, Operating Temp: -20 to 100°C,

Shore hardness at 80±5°, Tensile strength after ageing 100 kg/cm², Compression set least 30% min

SELECTION TABLE										
Pipe Size O.D.		RSI Width mm	T = Insulation Thickness = RSI Thickness							
Steel	Copper		13mm	19mm	25mm	32mm	38mm	50mm	63mm	75mm
	15mm	25mm	X		X					
1/2"	22mm	25mm	X		X	X				
3/4"	28mm	25mm	X	X	X	X	X	X		
1"	35mm	25mm	X	X	X	X	X	X	X	X
1 1/4"	42mm	25mm		X	X	X	X	X		
1 1/2"		25mm		X	X	X	X	X	X	X
	54mm	25mm		X	X	X				
2"		25mm		X	X	X	X	X	X	X
	67mm	25mm		X	X	X				
2 1/2"	76mm	38mm		X	X	X	X	X	X	X
3"		38mm		X	X	X	X	X	X	X
	108mm	38mm			X		X	X		
4"		38mm			X		X	X	X	X
5"	141mm	38mm			X		X	X	X	X
	159mm	50mm			X					
6"		50mm			X		X	X	X	X
8"		50mm			X		X	X	X	X
10"		50mm			X		X	X	X	X
12"		50mm						X	X	X
14"		50mm						X		

Notes: 1. Sizes marked "X" are available as standard. Other sizes available on request. 2. Please specify pipe OD and insulation thickness while ordering.